

Induktive Näherungsschalter, 2-Draht

Inductive proximity switches, 2-wire
 Finecorsa di prossimità induttivi, 2-fili
 P+F NBB3-V3-Z4

EPP2I-9
EPE2I-9
EAP2I-9
EAE2I-9

Varianten (Versions / Tipi)



Model EPP (S. 1)



Model EPE (S. 2)



Model EAP (S. 5)




Model EAE (S. 6)

Technische Daten (Technical features / Dati tecnici)

Endschalterfabrikat Producer switch / Marca finecorsa	P+F
Endschaltertyp Switch type / Tipo finecorsa	NBB3-V3-Z4 (2-wire)
Spannung Voltage / Tensione	5-60V DC
Stromaufnahme Current / Corrente	4-100mA
Schaltfrequenz Frequency / Frequenza	2000Hz
Anzeige Output indicator / Indicazione	LED gelb (yellow / giallo)
Schutzart Schalter Enclosure switch / Protezione finecorsa	IP67 - DIN 40050
Temperatur Temperature / Temperatura	-25°C ... +70°C

Anschlussbild EP/EA

Connection / Connessione



Adaption (Adoption / Adattamento)

Code code codice	Bohrbild Antrieb Hole spacing act. Foratura attuatore	Wellenhöhe Antrieb Shaft height act. Altezza perno att.	P = Polyamid Polyamide Poliammide	E = Edelstahl Stainless steel Acciaio Inox
00	50 x 25 mm	20 mm	x	x
01	80 x 30 mm	20 mm	x	x
02	80 x 30 mm	30 mm	x	x
03	130 x 30 mm	30 mm	x	x
04	130 x 30 mm	50 mm		x
05	80 x 30 mm	40 mm		x
06	80 x 30 mm	50 mm		x
07	130 x 30 mm	20 mm	x	x
08	130 x 30 mm	40 mm		x
09	50 x 25 mm	30 mm	x	x
10	Ohne Brücke Without bracket / Senza bracket			

Schaltertyp

Switch type / Tipo finecorsa



Artikelnummer (Code number / Numero codice)

Preisliste Seite 2 Price list page 2 / Listino dei prezzi pagina 2

